

CERTIFICATE OF EMC

CERTIFICATE NO.: SET2015-01561

Product: Landing call and 5.6 Inches LCD display board
Model: BL2000-HEH-M* (*=2-2.99, indicate the different customer or/and Software function number)
Applicant: ShenYang Bluelight Automatic Technology Co., Ltd.
Address: No. 37 Shiji Road, Hunnan New District, Shenyang, China

This is to certify that, on the basis of the tests undertaken as per Report No. **SET2015-01561**, the submitted sample of the above item complies with:

EN61000-6-4:2007+A1:2011

EN61000-6-2:2005

and fulfils testing requirement of the EMC directive 2004/108/EC



Signed for and on behalf of
CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.

Wu Li An

Wu Li An, Vice Director

Date of Issue: Feb. 06, 2015



CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.


Building 28/29, Shiguo Road, Houzhan Area, Nanshan District,

Shenzhen, Guangdong, China

Tel:86-755-26627338 Fax:86-755-26627238 <http://www.ccic-set.com>



Report No. 2015-01561



查询码: 6PA7ZR5b

Report No.




Table of Contents

Report.....	2
1 General Information	5
1.1 Description of EUT	5
1.2 Objective	5
2 Test Facilities and Configuration	5
2.1 Environmental Conditions	5
2.2 Measurement Uncertainty	5
2.3 Test Standards and Results	5
2.4 List of Equipments Used	5
3 Emission Test	8
3.1 EUT Setup and Operating Conditions	8
3.2 Radiated Disturbance Measurement	8
3.2.1 Limits of Radiated Disturbance	8
3.2.2 Test Setup	8
3.2.3 Test Result	9
4 Immunity Test	11
4.1 EUT Setup and Operating Conditions	11
4.2 Performance Criteria	11
4.3 Electrostatic Discharge Immunity Test	11
4.3.1 Test Specification	11
4.3.2 Test Setup	12
4.3.3 Test Result	12
4.4 Radiated, Radio Frequency Electromagnetic Field Immunity Test	13
4.4.1 Test Specification	13
4.4.2 Test Setup	13
4.4.3 Test Result	14

4.5 Electrical Fast Transient/Burst Immunity Test.....	14
4.5.1 Test Specification	14
4.5.2 Test Setup	14
4.5.3 Test Result	15
4.6 Surge Immunity Test	15
4.6.1 Test Specification	15
4.6.2 Test Setup	15
4.6.3 Test Result	15
4.7 Immunity to Conducted Disturbances Induced by RF Fields	15
4.7.1 Test Specification	15
4.7.2 Test Setup	16
4.7.3 Test Result	16
4.8 Power Frequency Magnetic Field Immunity Test	17
4.8.1 Test Specification	17
4.8.2 Test Setup	17
4.8.3 Test Result	17
Appendix I Photographs of the EUT	18
Appendix II Photographs of EMC Test Configuration	19

1 General Information

1.1 Description of EUT

Product: Landing call and 5.6 Inches LCD display board
 Model No.: BL2000-HEH-M2.1
 Brand Name: /
 Serial No.: /
 Rating: Input: 24V DC
 Accessories: /

NOTE:

1. For more detailed features description about EUT, please refer to User's Manual.
2. Application model is BL2000-HEH-M* (*=2-2.99 indicate the different customer or Software function number). Models differences do not affect the performance of EMC. All tests were performed on Model BL2000-HEH-M2.1 and results represented other models.
3. The highest frequency of the internal source of EUT is below 108 MHz, so the radiated emission measurement shall be made up to 1GHz.

1.2 Objective

Perform ElectroMagnetic Interference (EMI) and ElectroMagnetic Susceptibility (EMS) tests for CE Marking.

2 Test Facilities and Configuration

2.1 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

2.2 Measurement Uncertainty

The uncertainty is calculated using the method suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

- Uncertainty of Radiated Emission, $U_c = \pm 4.7 \text{ dB}$

2.3 Test Standards and Results

The EUT has been tested according to the following specifications:

EMISSION		
Standard	Test Type	Result
EN61000-6-4:2007+A1:2011	Radiated disturbance	PASS
IMMUNITY (EN61000-6-2:2005)		
Basic Standard	Test Type	Result
IEC 61000-4-2	Electrostatic discharge immunity	PASS
IEC 61000-4-3	Radiated, radio frequency electromagnetic field immunity	PASS
IEC 61000-4-4	Electrical fast transient/burst immunity	PASS
IEC 61000-4-5	Surge immunity	PASS
IEC 61000-4-6	Immunity to conducted disturbances induced by RF fields	PASS
IEC 61000-4-8	Power frequency magnetic field immunity	PASS

2.4 List of Equipments Used

Description	Manufacturer	Model No.	Calibration Date	Serial No.
Test Receiver	ROHDE&SCHWARZ	ESCI	Jun.10, 2015	A0902601
Broadband Ant. Anechoic Broadba5	ROHDE&SCHWARZ	VULB 09160	Jun.10, 2015	A0805560

3 Emission Test

3.1 EUT Setup and Operating Conditions

The EUT was powered by 24V DC mains. The EUT was continuously operated during the test.


3.2 Radiated Disturbance Measurement

3.2.1 Limits of Radiated Disturbance

Frequency range (MHz)	Quasi peak limits(dB μ V/m), at 10m measurement distance
30 – 230	40
230 - 1000	47

Notes:

- (1) The lower limit shall apply at the transition frequency.
- (2)



1. Electromagnetic radiation disturbances, max detector, antenna polarization: Vertical

2. Electromagnetic radiation disturbances, max peak detector, antenna polarization: Horizontal

4 Immunity Test

4.1 EUT Setup and Operating Conditions


Same as 3.1.

4.2 Performance Criteria

Criterion A	The apparatus shall continue to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.
Criterion B	The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.
Criterion C	Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

4.3 Electra





4.4.3 Test Result

Frequency	Polarity	Azimuth	Field Strength (V/m)	Observation	Comply with Criterion
80-1000 MHz	V&H	0,90, 80, 270	10	Note(1)	A
1.4-2.0GHz	V&H	0,90, 80, 270	3	Note(1)	A
2.0-2.7GHz	V&H	0,90, 80, 270	1	Note(1)	A



4.7 Immunity to Conducted Disturbances Induced by RF Fields

4.7.1 Test Specification

Basic Standard:	IEC 61000-4-6
Frequency Range:	0.15 MHz – 80 MHz
Field Strength:	10V
Modulation:	1 kHz Sine Wave, 80%, AM Modulation

4.8 Power Frequency Magnetic Field Immunity Test

4.8.1 Test Specification

Basic Standard:	IEC 61000-4-8
Frequency Range:	50Hz

Appendix I Photographs of the EUT



Appendix II Photographs of EMC Test Configuration

1. Radiated Field Strength Measurement

2. Electrostatic Discharge Immunity Test

3. Radiated, Radio Frequency Electromagnetic Field Immunity Test (below 1GHz)

4. Radiated, Radio Frequency Electromagnetic Field Immunity Test (above 1GHz)

5. Electrical Fast Transient/Burst Immunity Test

6. Surge Immunity Test



7. Immunity to Conducted Disturbances Induced by RF Fields

8. Power Frequency magnetic Field Immunity



STATEMENT

This test laboratory is accredited by CNAS, Accreditation Certificate No. L1659.

2.